

Rubio Monocoat Exterior Wood Cleaner

Rubio Monocoat Exterior Wood Cleaner is a preparatory cleaner for all types of exterior wood (wooden patios, fences, exterior doors, carports, terraces, etc.) and composite. The product removes grey discolouration, green deposits and dirt.



PRODUCT INFORMATION

> Specific characteristics

> Benefits

- New wood:
 - Grease that appears naturally in some types of wood is removed.
 - The pores are opened, this guarantees that the protective layer will last longer.
- Wood previously treated with another brand's product:
 - For saturation products applied to the wood longer than a year: Exterior Wood Cleaner will remove all residues from previous treatments.
 - If a paint or varnish has been applied, the surface must be sanded, stripped or sand-blasted first. Attention: After sand-blasting, the consumption of the finishing oil increases.

> Technical characteristics

• Physical state: liquid • Colour: transparent • Odour: characteristic

• pH: 1,3

• Density: 0,99 kg/L

> Storage

The product can be stored for up to 12 months. Store in dry conditions and in the original packaging. Keep away from frost.

TECHNICAL DATA SHEET

EXTERIOR



APPLICATION INFORMATION

> Instructions for use

- **STEP 1.** Dampen the surface with water. Use a garden hose.
- STEP 2. Apply some undiluted Exterior Wood Cleaner.
- STEP 3. Scrub the treated area with a nylon scrubbing brush in the lengthwise direction of the wood until it is clean. This will cause the product to foam. For stubborn stains, repeat the treatment.
- STEP 4. Rinse thoroughly until all the foam has disappeared.
- STEP 5. Allow the surface to dry well (± 30 minutes at a temperature of 20°C and proper ventilation).
- STEP 6. Treat with the Rubio Monocoat exterior wood protection product of your choice.

' Tips & Tricks

A good preparation is crucial to ensure a lasting protective finish. All new, greyed, and previously treated wood must always be treated beforehand with Exterior Wood Cleaner.

> Packaging

- Bottle 100 ml
- Jerrycan 1 L

Consumption

Manual: ± 15 m²/L

^{*} These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.







Check the packaging and the safety data sheet for more details.

For our complete assortment of products for the protection and colouring of interior and exterior wood, please visit www.rubiomonocoat.com

LIABILITY: It is the user's responsibility to establish, through his own tests, whether the product is suitable for the chosen application. In no case can Muylle Facon NV be held liable for any consequential damage. The information above may be subject to changes, which will be published in the updated versions of the technical data sheet. We cannot be held liable for poor results due to causes that are not related to the quality of the product. This technical information has been drawn up based on the currently available information and knowledge. The most recent technical data sheets can be requested or are available on the website. Date of TDS: 15/04/2022. Check the safety information before using the product.







Ambachtenstraat 58 8870 Izegem (BELGIUM)

Phone +32 (0) 51 30 80 54 Fax +32 (0) 51 30 99 78 info@muyllefacon.be

www.rubiomonocoat.com